

General features



Disclaimer:
Images are purely indicative. The features and the accessories of the products may differ according to model and application.

Temperature range	Adjustable +2°C / +15°C for both compartments
Factory setpoint Increment	+5°C 0.1°C for both compartments
Ambient working class Climatic class	From +16°C to +38°C N-ST
Nominal capacity	700 + 700 lt (24,7 + 24,7 cu ft)
Gross capacity Net capacity	620 + 620 lt (21,9 + 21,9 cu ft) 620 + 620 lt (21,9 + 21,9 cu ft)
External dimensions (WxDxH)	150 (75 + 75)x84,5x210 cm
Internal dimensions (WxDxH)	60x68,5x150 cm (X2)
Net weight without any internal fittings	288 kg
Package dimensions Weight	No. 2 cardboards on pallet 77x90x214 cm each weight 161 kg each No. 2 wooden crates on pallet 84x94x214 cm each weight 174 kg each
Structure	No. 2 monocoque type body, made of plasticized, non-toxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Rounded corners and tray-type inner bottom.
Insulation type	High density (43 kg/m ³) in-walls injected PUF, without any CFC, environmental-friendly, water-foam based.
Insulation thickness	75 mm
Feet	No. 4 adjustable feet
Door	No. 2 doors made of tempered glass, triple thickness, self-closing thanks to the spring hinge and 90° stop position.
Lightning	Full LED, all length of inner chamber, automatic switching on at door opening or from the display when the door is closed.
Internal fittings	Customizable and height adjustable, it can mix independently: wire shelves supported by adjustable clips (dim.cm 56x65) fully extractible drawers made of aluminium, with dividers (WxDxH): cm 15x60x7,5 (nr 3 compartments) fully extractible drawers made of aluminium, without dividers (WxDxH): cm 49x60x7,5 st. steel wire basket on telescopic slides (WxDxH): cm 53,8x63x14,8 st. steel wire drawers on telescopic slides (WxDxH): cm 53,8x60,5x6,2 st. steel wire shelves supported by adjustable clips (dim.cm.56x66)
Suggested internal fittings	No. 8 wire shelves (8 + 8)

Refrigeration system

Refrigeration	Professional, ventilated, forced, hermetic compressor type. No. 2 separate and independent cooling systems, one for each compartment.
Defrost	Automatic, adaptive, including condensate water vaporisation
Refrigerant	Natural R290
GWP ODP	3 0

Electronic controller



Controller	ECT-F PLUS controller
Type of controller	Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C
Power switch	Integrated in user's interface
Security features	Settable user password Visual and acoustic for temperature alarms and failures such as: Open door High temperature High temperature caused by power failure.
Alarm system	Low temperature Power failure (alarm back up up to 48h) Clogged condenser Faulty batteries Any functional failure/faulty parts
Data and event recordings	Last 12 events available on the display
Settable temperature alarm limits	Yes, through parameter adjustment
Control sensors	NTC type probes
Connection for remote alarm signalisation	Ready on the board, remote on request
Temperature recording	Log of minimum and maximum temperature reached, manual reset
Data export	Not available

Electrical and functional data

Standard power supply	230V / 1ph / 50Hz
Standard plug type	Schuko type "G"
Compressor protection	Overload Protector included
Power absorption/current	kW 0,12 + 0,12 (Amp 0,7 + 0,7)
Inrush current	Amp 2,5 + 2,5
Noise level	<50 + 50 dBA
Heat emission according to EN 12900	W 40 + 40
Hold over time at 20°C ambient (air)	5 h (from +5°C to +15°C)
Energy consumption at 20°C ambient	1 + 1 kWh/24h

Conformity

Directives and regulations	Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH
Available certificate	CE
Application environment	Non-flammable, non-explosive, non-corrosive, with adequate air exchange

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

Lock with key

External dry contact

Anty-freeze safety

DIN 13277 conformity (includes anty-freeze safety)

Includes: anti-freezer safety, key lock, buffer batteries for power failure alarm and external terminal board with dry contact

Temperature chart recorder

Solid type door

Please refer to LABOR series

Additional wire shelf kit

Extractible drawer on telescopic slides

Extractible drawer without inner dividers on telescopic slides

St. steel wire shelf kit

St. steel wire drawer on telescopic slides

St. steel wire basket on telescopic slides

Perforated stainless steel shelf

Lockable drawer for narcotics H mm 100

Rack 140x500x150H mm (max 3 per each shelf)

Plexiglas front panel for extractible drawer

Castors kit with brakes

Internal Socket (no.1)

35 mm access port with stopper

Port hole mm 15

Humidity sensor

PT100 sensor with free contacts

Mains voltage stabilizer

Non-standard plug and cable

Power 220V/60Hz

Power 115V/60Hz

Wooden crate package

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it