

## **Product technical data sheet**

# **ULTRAFREEZER 820**

Cod. ULV0821

### **Characteristics**



Images are purely indicative. The features and the accessories of the products may differ according to model and application.

Temperature range	-50°C / -86°C
Capacity	820 lt (28,96 cu ft)
External dimensions (WxDxH)	cm 134x89x199,2 Internal Dimensions (WxDxH) cm 103,5x62,6x127,6; Weight 390kg
Structure and insulation	Stainless steel 18/10 AISI 304 inside and pre-coated steel white colouroutside; insulation polyurethane thickness 130 mm
Door	Nr. 1 blind door pre-coated steel white colour + nr. 2 hinged inner-doors
Key lock	
Rollers	Castors with brakes
Internal equipment	Nr.3 shelves + bottom
Controller	Digital electronic thermostat with 7" touchscreen
Alarms	Acoustic and visual far temperature deviations (high and low), door open, condenser high temperature, failures, power failure and low battery. The alarm system is fed by an automatic recharging battery, so it can work also during a power failure.
Data and event recording	Daily temperature graph always available on the 7" Touchscreen. Inner memory of the last 180 days, with download from USB port (software included).
Connectivity	USB port; Dry Contact; Ethernet port RJ45
Pass trough port mm 26	
Refrigeration Type	Static

	Technical data
Technical Data	<ul> <li>Nr.2 compressors, cascade system</li> <li>Refrigerant type: R455A in the first stage; R170 in the second one. Gas CFC free.</li> <li>Mains Voltage 230V/1/50Hz</li> <li>Daily consumption: 14 kWh/24H</li> <li>Instant power consumption: 1,29 kW (6,9 A)</li> <li>Heat emission: 550 W</li> <li>Noise leve!: &lt;57 dBA</li> <li>Ambient Temperature: +10/+25 °C; humidity 60%</li> <li>Connector: Schuko</li> </ul>
In accordance with	2014/30/UE, 2014/35/UE, 2011/65/UE (ROHS II) and following modifications
Package	Wooden case <i>Dim. cm.154x107x225</i> ; <i>Kg.555</i>

# Accessories

Additional Shelf		
PTIOO probe (free contacts)		
CO2 Back-up system		
LN2 Back-up system		
High pressure tube 2 mt or 1 mt		
Stainless steel storage racks		
Storage boxes realized in water-proof cardboard		
Cryo-gloves		
60 Hz Frequency		
115 V		