

Characteristics



Temperature Range	-10/-60 °C
Capacity	230 lt (8,13 cu ft)
External Dimensions (WxDxH)	cm 105,5x73x86,5 <i>Internal Dimensions (WxDxH) cm 85x45x65 (+ 20x45x40);</i>
Weight	Kg 64
Structure and insulation	White coated steel inside and outside, thickness 100 mm
Feet	n.4 feet
Door	n. 1 lid
Key Lock	
Controller	Digital electronic thermostat
Alarms	Acoustic and Visual for temperature deviations
Refrigeration Type	Static
Defrost	Manual

Technical data

Details	<ul style="list-style-type: none"> Refrigerant type: Completely eco-friendly mixture of refrigerant gases CFC free Mains Voltage 230V/1/50Hz Instant power consumption: 0,41 kW (4 A) Noise level < 50 dB Ambient Temperature: +10/+32 °C; humidity 60% Connector: Schuko
In accordance with	2014/30/CE, 2014/35/CE and following modifications
Package	Strong Cardboard on wooden pallet Dim. cm. 110x80x110; Kg.74 <i>Wooden crate on wooden pallet available: dim. cm.125x90x112; Kg.106</i>

Images are purely indicative. The features and the accessories of the products may differ according to model and application.

Castors (of which 2 with brakes) - H +11 cm

Internal steel wire basket (max n.2)

dimensions WxDxH cm 40x25x15

Voltage stabilizer

Frequency 60 Hz

Voltage 115 V

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) - Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it